

Panasonic

ideas for life



AJ-PCD30

Memory Card Drive "P2 drive"

Scheduled for release in August 2011

Preliminary



The New P2 drive with Super Speed USB 3.0 Interface Boosts Workflows for News and Other Productions

The AJ-PCD30 is a new P2 drive with a USB 3.0 interface that connects to a PC's USB 3.0 port and transfers data at 1.5 Gbps or higher.* With a super speed interface, the AJ-PCD30 takes full advantage of the P2 card's speedy read/write performance. It dramatically accelerates file uploading in editing and transmission processes, to improve the workflow for news and other programs, and HD productions in particular. It allows quick, efficient news reporting. Three P2 card slots allow the data from three cards to be simultaneously transmitted to a PC or nonlinear editor. The AJ-PCD30 can be externally connected to a PC or built in to the 5 type bay of a Windows® PC.

*When using multiple E Series P2 cards. The actual transfer rate varies depending on the file being transferred, the system, the application software, the P2 card version and other conditions. If the PC does not have a USB 3.0 interface, data is transferred via USB 2.0. The P2 card driver software (provided with the product or downloadable for free) must be installed to read data from or write data to P2 cards.

About USB 3.0 – SuperSpeed USB

USB 3.0 is the newest USB (Universal Serial Bus) standard for connecting PCs and peripheral devices. The official specifications for Version 1.0 were released in 2008, and products with USB 3.0 became available from the end of 2009. Commonly called SuperSpeed USB, USB 3.0 offers a maximum data transfer rate of 5 Gbps, which is more than ten times faster than USB 2.0. The bus power capacity was also increased to 900 mA maximum as compared to 500 mA for USB 2.0. The USB 3.0 standard is downward-compatible, so a USB 3.0 device can be connected to a USB 2.0 or earlier standard port, but the transfer performance will be limited to that of the lower standard port. To distinguish the USB 3.0 connector from that of the USB 1.1/2.0, the insulator section of the USB 3.0-compatible connector is generally blue.

AJ-PCD30 — New P2 drive with USB 3.0 Interface

USB 3.0 Interface for High-Speed Data Transfer

The USB 3.0 interface lets you transfer P2 files at 1.5 Gbps or higher* when connected to a USB 3.0-compatible PC.

USB 2.0 Compatibility

Since USB 3.0 is downward-compatible with earlier USB standards, the AJ-PCD30 can connect directly to USB 2.0 compatible PC and transfer data at the USB 2.0 transfer rate.

3-slot P2 drive

The three P2 card slots on the AJ-PCD30 let you mount three cards simultaneously.

External Connection or Built-in Use

The supplied AC adaptor allows the AJ-PCD30 to be used as a standalone drive. It can also be built in to the 5 type bay of a Windows PC.

*When using multiple E Series P2 cards. The actual transfer rate varies depending on the file being transferred, the system, the application software, the P2 card version and other conditions. If the PC does not have a USB 3.0 interface, data is transferred via USB 2.0. The P2 card driver software (provided with the product or downloadable for free) must be installed to read data from or write data to P2 cards.



Specification

Power Source:	DC 16 V 0.6 A with AC adaptor, DC 12 V 0.8 A when PC built-in
AC Adaptor:	AC 100 V to 240 V, 50 Hz/60 Hz
Weight:	approx. 1.2 kg (2.6 lb)
Operating Temperature:	0°C to 40°C (32°F to 104°F)
Operating Humidity:	10% to 80% (non condensation)
Dimensions (W x H x D):	148.4 mm x 42.5 mm x 199.5 mm (5-7/8 inches x 1-11/16 inches x 7-7/8 inches) excluding protruding parts (Compatible with 5 type bay of a Windows PC.)

PC System Requirement

OS:	Microsoft® Windows 7 Professional (SP1), Ultimate (SP1) 32 bit/64 bit Microsoft Windows Vista® Business (SP2), Ultimate (SP2) 32 bit/64 bit Microsoft Windows XP Professional (SP3) 32 bit Mac OS X 10.5, 10.6 Intel® processor
Main Memory:	1 GB or more memory
Accessory:	AC Adaptor, CD-ROM (USB 3.0 cable is not included.)

Weight and dimensions shown are approximate.
Specifications are subject to change without notice.

Panasonic®

(Countries and Regions)

Panasonic Corporation
Digital Imaging Business Group
2-15 Matsuba-cho, Kadoma, Osaka 571-8503
Japan
<http://pro-av.panasonic.net/>

Argentina	+54 1 308 1610	Lebanon	+96 11665557	Taiwan	+886 2 2227 6214
Australia	+61 2 9986 7400	Malaysia	+60 3 7809 7888	Thailand	+66 2 731 8888
Bahrain	+973 252292	Mexico	+52 55 5488 1000	Turkey	+90 216 578 3700
Belgium	+32 (0) 2 481 04 57	Netherlands	+31 73 64 02 577	U.A.E. (for all Middle East)	+971 4 8862142
Brazil	+55 11 3889 4035	New Zealand	+64 9 272 0100	Ukraine	+380 44 4903437
Canada	+1 905 624 5010	Norway	+47 67 91 78 00	U.K.	+44(0)1344 70 69 13
China	+86 10 6515 8828	Pakistan	+92 5370320 (SNT)	U.S.A.	+1 877 803 8492
Hong Kong	+852 2313 0888	Palestine	+972 2 2988750	Vietnam	+848 38370280
Czech Republic	+420 236 032 552/511	Panama	+507 229 2955		
Denmark	+45 43 20 08 57	Peru	+51 1 614 0000		
Egypt	+20 2 23938151	Philippines	+63 2 633 6163		
Finland, Latvia, Lithuania, Estonia	+358 (9) 521 52 53	Poland	+48 (22) 338 1100		
France	+33 (0) 1 55 93 66 67	Portugal	+351 21 425 77 04		
Germany, Austria	+49 (0)611 235 0	Puerto Rico	+1 787 750 4300		
Greece	+30 210 96 92 300	Romania	+40 21 211 4855		
Hungary	+36 (1) 382 60 60	Russia & CIS	+7 495 6654205		
India	+91 120 247 1000	Saudi Arabia	+96 626444072		
Indonesia	+62 21 385 9449	Singapore	+65 6270 0110		
Iran (Vida)	+98 21 2271463	Slovak Republic	+421 (0) 2 52 92 14 23		
(Panasonic Office)	+98 2188791102	Slovenia, Albania, Bulgaria, Serbia, Croatia, Bosnia, Macedonia, Montenegro	+36 (1) 382 60 60		
Italy	+39 02 6788 367	Spain	+27 11 3131622		
Jordan	+962 6 5859801	Switzerland	+41 (0) 41 259 96 32		
Kazakhstan	+7 727 298 0891	Sweden	+46 (8) 680 26 41		
Korea	+82 2 2106 6641	Switzerland	+41 (0) 41 259 96 32		
Kuwait	+96 522431385	Syria	+963 11 2318422/4		



Factories of Systems Business Group have received ISO14001:2004-the Environmental Management System certification. (Except for 3rd party's peripherals.)