

Bright SOLID SHINE Laser LCD Projectors Blend High Performance and Low Running Costs for Best Value in Mid-sized Venues



PT-MZ770 Series					
	PT-MZ770	PT-MZ770L	PT-MZ770LB*	PT-MW730	PT-MW730L
Brightness	8,000 lm				
Resolution	WUXGA			WXGA	
Contrast	3,000,000:1*1				
Cabinet Color	White		Black	White	
Lens	With supplied lens	Without lens		With supplied lens	Without lens

*PT-MZ770LB is only available in Americas and Europe.

Outstanding Brightness and Picture Quality

- SOLID SHINE Laser technology with 3LCD optical engine serves bright, vivid, and detailed pictures
- Up to 8,000 lm brightness delivered from compact and lightweight body
- 3,000,000:1*1 dynamic contrast via digitally modulated laser light source improves text legibility and assists with crisp and accurate pictures
- Available in WUXGA*2 for detailed Full HD video reproduction and high-resolution images, text, and graphics
- Detail Clarity Processor 4 enhances image clarity and sharpness
- Daylight View Basic optimizes pictures for best visibility in bright environments
- DICOM Simulation Mode*3 for medical presentations
- Color Adjustment Function corrects color variations in multi-projector applications

High Efficiency and Low Maintenance

- Laser light source returns 20,000 hours*4 of continuous operation (no exchange required)
- Inorganic LCD panels and inorganic polarizing plates maintain high image quality for extended periods
- Extended 20,000-hour*5 maintenance-free period for reusable Eco Filter*6
- One-way airflow design improves efficacy of lens-assembly sealing to maintain high brightness and picture quality
- Dust-resistant cabinet design improves filter-module and air-intake-duct sealing
- ECO Management System effectively reduces power consumption

Easy Setup and Operation

- DIGITAL LINK/HDMI® support transmission of uncompressed 4K signals (PT-MZ770/L only)
- Powered lens shift, zoom, and focus via remote control
- Supports wireless projection with optional module (ET-WM300)
- Corner Keystone & Curved Screen Correction
- Network function via LAN for stress-free remote operation
- Supports free Multi Monitoring & Control Software
- Incorporates LinkRay™ Light ID Transmission function delivering information to smartphones*7, ideal for signage and exhibition/display applications

*1 With Dynamic Contrast 1/2, Image Mode set to Dynamic. *2 PT-MZ770/L has WUXGA and PT-MW730/L WXGA resolution. *3 This product is not a medical instrument. Do not use for actual medical diagnosis. *4 Around this time, original light source brightness will have decreased by approximately 50%. With IEC62087:2008 Broadcast content, Dynamic Contrast [2], in environments with 0.15 mg/m³ of particulate matter. Estimated maintenance time varies depending on environment. *5 In environments with 0.15 mg/m³ of particulate matter. Estimated maintenance time varies depending on environment. *6 Eco Filter is designed to be washed and reused twice. If filter is not sufficiently clean after washing with water, replacement is advised. *7 Requires purchase and activation of a LinkRay™ service contract.

Specifications (Tentative)

Model	PT-MZ770/MZ770L		PT-MW730/MW730L		
LCD panel	Panel size	19.3 mm (0.76") diagonal (16:10 aspect ratio)			
	Display method	Transparent LCD panel (x 3, R/G/B)			
	Drive method	Active matrix			
Lens	PT-MZ770/MW730: Powered zoom (throw ratio 1.6–2.8:1), F = 1.7–2.3, f = 26.8–45.5 mm PT-MZ770L/MW730L: Optional powered zoom/focus lenses				
Light source	Laser diode (Class 1) (Class 3R for US models)				
Screen size (diagonal)	1.02–10.16 m (40–400 in), 16:10 aspect ratio 1.52–10.16 m (60–400 in) with the ET-ELW22, 16:10 aspect ratio				
Brightness*1	8,000 lm				
Center-to-corner uniformity*1	90 %				
Contrast	3,000,000:1 (Dynamic Mode/Dynamic Contrast 1/2)				
Resolution	1920 x 1200 pixels		1280 x 800 pixels		
Optical axis shift	Vertical (from center of screen)	±67 % (powered) (for supplied lens [ELS20]/ELW20/ELT22/ELT23, ELW22; max. ±60 %, ELW21; cannot use optical axis shift function)			
	Horizontal (from center of screen)	±35 % (powered) (for supplied lens [ELS20]/ELW20/ELT22/ELT23, ELW22; max ±30%, ELW21; cannot use optical axis shift function)			
Keystone correction range*2	Vertical: ±25°, Horizontal: ±30°		Vertical: ±35°, Horizontal: ±35° When vertical and horizontal keystone are used simultaneously, correction cannot be made exceeding total of 55°.		
Installation	Horizontal/Vertical, free 360-degree installation				
Terminals	HDMI 1/2 IN	HDMI 19-pin x 2 (Compatible with HDCP 2.2, Deep Color), audio signal: Linear PCM (Sampling frequency: 48 kHz/44.1 kHz/32 kHz)		HDMI 19-pin x 2 (Compatible with HDCP, Deep Color), audio signal: Linear PCM (Sampling frequency: 48 kHz/44.1 kHz/32 kHz)	
	RGB 1 IN	RGB x 1 (BNC x 5): RGB/YPbPr/YCbCr			
	RGB 2 IN	D-sub HD 15-pin (female) x 1: RGB/YPbPr/YCbCr			
	VIDEO IN	Pin jack x 1			
	MONITOR OUT	D-sub HD 15-pin (female) x 1: RGB/YPbPr/YCbCr			
	AUDIO IN 1/2	M3 stereo mini jack (L-R) x 2			
	AUDIO IN 3	Pin jack x 2 (L-R) x 1			
	SERIAL IN	D-sub 9-pin (female) x 1 for external control (RS-232C compliant)			
	REMOTE 1 IN	D-sub 9-pin (female) x 1 for external control (parallel)			
	REMOTE 2 IN	M3 x 1 for wired remote control			
	LAN	RJ-45 x 1 for network connection, 10Base-T, 100Base-TX, compatible with PjLink™ (Class 2)			
	DIGITAL LINK/LAN	RJ-45 x 1 for network and DIGITAL LINK connection HDBase-T™ compliant (Compatible with PjLink™, HDCP 2.2, Deep Color)		RJ-45 x 1 for network and DIGITAL LINK connection HDBase-T™ compliant (Compatible with PjLink™, HDCP, Deep Color)	
	Viewer/Pairing	USB (Type A) x 1			
	DC OUT	USB (Type A) x 1 for power supply (DC 5 V/max. of 2 A*)			
	Power supply	100–240 V AC, 50/60 Hz			
Power consumption	570 W		545 W		
Built-in speaker	10 W (monaural)				
Operating noise*1	35 dB (NORMAL/ECO), 28 dB (QUIET)				
Filter	x 1, estimated maintenance time: approx. 20,000 hours*4				
Cabinet materials	Molded plastic (PC + ABS)				
Dimensions (W x H x D)	PT-MZ770/MW730: 560 x 205*5 x 443 mm (22 1/16" x 8 1/16"*5 x 17 7/16") (with supplied lens) PT-MZ770L/MW730L: 560 x 205*5 x 428 mm (22 1/16" x 8 1/16"*5 x 16 27/32") (without lens)				
Weight*6	PT-MZ770/MW730: Approximately 17.1 kg (37 lbs) (with supplied lens) or less PT-MZ770L/MW730L: Approximately 16.3 kg (35.7 lbs) (without lens)				
Operating environment	Operating temperature: 0 °C–45 °C (32 °F–113 °F)*7, operating humidity: 20 %–80 % (no condensation)				
Applicable software/application	Wireless Manager for Windows/Mac, Logo Transfer Software, Multi Monitoring & Control Software, Smart Projector Control for iOS/Android™, Plug and Share, Wireless Projector Apps for iOS/Android™				

Note: PT-MZ770L and PT-MW730L deliver the same performance as PT-MZ770 and PT-MW730 respectively, but come without a lens.

*1 Measurement, measuring conditions, and method of notation all comply with ISO/IEC 21118: 2012 international standards. *2 With supplied lens. Value differs when correction for both directions is operated. *3 On standby, power supply is available with Quick Startup set to ON or Power Management set to Ready. *4 Under conditions with 0.15 mg/m³ of particulate matter (based on tests by the American Society of Heating, Refrigerating, and Air-Conditioning Engineers [ASHRAE], and the Japanese Building Maintenance Association). Estimated maintenance time varies depending on environment. *5 With legs at shortest position. *6 Average value. May differ depending on models. *7 Brightness is limited at operating temperatures exceeding 36 °C (96 °F), and projectors cannot be operated at altitudes higher than 2,700 m (8,858 ft) above sea level.

Optional Accessories

Zoom Lens

ET-ELW20 / ET-ELW22 /
ET-ELT22 / ET-ELT23

Fixed-Focus Lens

ET-ELW21

Ceiling Mount Bracket

ET-PKD120H (for high ceiling)
ET-PKD120S (for low ceiling)

Bracket Assembly

ET-PKE301B

Replacement Filter Unit

ET-RFM100

Wireless Module

ET-WM300

Easy Wireless Stick

ET-UW100*

* US, Canada, Australia, New Zealand,
Thailand, and Japan only.

DIGITAL LINK Switcher

ET-YFB200G

Digital Interface Box

ET-YFB100G

Early Warning Software

ET-SWA100 Series*

Note: Part number suffix may differ depending on the license type.

* Multi Monitoring & Control Software Ver. 2.0 or later is required.

Please download from the following website:

<https://panasonic.net/cns/projector/download/application/>

Panasonic®

Weights and dimensions shown are approximate. Specifications and appearance are subject to change without notice. Product availability differs depending on region and country. This product may be subject to export control regulations. PjLink™ is a registered trademark or pending trademark in Japan, the United States, and other countries and regions. The terms HDMI and HDMI High-Definition Multimedia Interface, and the HDMI Logo are trademarks or registered trademarks of HDMI Licensing Administrator, Inc. in the United States and other countries. All other trademarks are the property of their respective trademark owners. © 2018 Panasonic Corporation. All rights reserved.



For more information about Panasonic projectors, please visit:
Projector Global Website – panasonic.net/cns/projector
Facebook – www.facebook.com/panasonicprojector
YouTube – www.youtube.com/user/PanasonicProjector

All information included here is valid as of June 2018.

PT-MZ770PRE2 Printed in Japan.